



**Committee on  
Earth Observation  
Satellites**

## CEOS-ARD - Optical - Surface Reflectance

### Document Status

Product Family Specification, Optical, Surface Reflectance

Proposed revisions may be provided to: [ard-contact@lists.ceos.org](mailto:ard-contact@lists.ceos.org)

### Document History

Not available yet

### Contributing Authors

- Adam Lewis, Geoscience Australia, Australia
- Jonathon Ross, Geoscience Australia, Australia
- Andreia Siqueira, Geoscience Australia, Australia
- Darcie Bontje, USGS, USA
- Steve Labahn, USGS, USA
- Mary Metzger, USGS, USA
- Matt Steventon, LSI-VC Secretariat

# CEOS Analysis Ready Data Definition

---

*CEOS Analysis Ready Data (CEOS-ARD) are satellite data that have been processed to a minimum set of requirements and organized into a form that allows immediate analysis with a minimum of additional user effort and interoperability both through time and with other datasets.*

## Description

---

**Product Family Specification:** Optical, Surface Reflectance (SR)

**Version:** 5.1-draft

**Applies to:** Data collected by Optical sensors

## Background

---

Data collected with multispectral optical sensors operating in the VIS/NIR/SWIR wavelengths at all ground sample distances and resolutions.

# Definitions and Abbreviations

---

**CEOS-ARD**

Committee on Earth Observation Satellites - Analysis Ready Data

**DOI**

Digital Object Identifier

**NIR**

Near Infrared

**SI**

International System of Units, internationally known by the abbreviation SI (from French Système international d'unités)

**SR**

Surface Reflectance

**SWIR**

Shortwave Infrared

**VIS**

Visible

# Requirements

---

**WARNING:** The section numbers in front of the title (e.g. 1.1) are not stable and may change or may be removed at any time. Do **not** use the numbers to refer back to specific requirements! Instead, use the textual identifier that is provided below the title.

## 1. General Metadata

---

These are metadata records describing a distributed collection of pixels. The collection of pixels referred to must be contiguous in space and time. General metadata should allow the user to assess the *overall* suitability of the dataset, and must meet the requirements listed below.

### 1.1. Traceability

Identifier: `meta.metadata-traceability`

**Threshold requirements:**

Not required.

**Goal requirements:**

Data must be traceable to SI reference standard.

Notes:

1. Relationship to Section “[Radiometric and Atmospheric Corrections: Measurement Uncertainty](#)”. Traceability requires an estimate of measurement uncertainty.
2. Information on traceability should be available in the metadata as a single DOI landing page.

## 2. Source Metadata

---

These are metadata records describing (detailing) **each** acquisition (source data) used to generate the ARD product. This may be one or multiple acquisitions.

### 2.1. Example Requirement

Identifier: `src.example`

This is an example requirement.

**Threshold requirements:**

This is a threshold requirement.

## **Goal requirements:**

This is a goal requirement.

Notes:

1. This is a note.

## **3. Product Metadata**

---

Information related to the CEOS-ARD product generation procedure and geographic parameters.

### **3.1. Example Requirement**

Identifier: prd.example

This is an example requirement.

## **Threshold requirements:**

This is a threshold requirement.

## **Goal requirements:**

This is a goal requirement.

Notes:

1. This is a note.

## **4. Per-Pixel Metadata**

---

The following minimum metadata specifications apply to each pixel. Whether the metadata are provided in a single record relevant to all pixels or separately for each pixel is at the discretion of the data provider. Per-pixel metadata should allow users to discriminate between (choose) observations on the basis of their individual suitability for applications.

*Cloud optimized file formats are recommended.*

### **4.1. Example Requirement**

Identifier: ppx.example

This is an example requirement.

## **Threshold requirements:**

This is a threshold requirement.

### **Goal requirements:**

This is a goal requirement.

Notes:

1. This is a note.

## **5 . Radiometric and Atmospheric Corrections**

---

The following requirements must be met for all pixels in a collection. The requirements indicate both the necessary outcomes and the minimum steps necessary to be deemed to have achieved those outcomes. Radiometric corrections must lead to a valid measurement of surface reflectance.

### **5 . 1. Measurement Uncertainty**

Identifier: rac.measurements-uncertainty

Note: In current practice, users determine fitness for purpose based on knowledge of the lineage of the data, rather than on a specific estimate of measurement uncertainty.

#### **Threshold requirements:**

Not required.

#### **Goal requirements:**

An estimate of the certainty of the values is provided in measurement units.

Notes:

1. This is a requirement for SI traceability. See also Section “[General Metadata: Traceability](#)”.
2. Information on measurement uncertainty should be available in the metadata as a single DOI landing page.

## **6 . Geometric Corrections**

---

The geometric corrections are steps that are taken to place the measurement accurately on the surface of the Earth (that is, to geolocate the measurement) allowing measurements taken through time to be compared. This section specifies any geometric correction requirements that must be met in order for the data to be analysis ready.

## 6.1. Example Requirement

Identifier: gcor.example

This is an example requirement.

**Threshold requirements:**

This is a threshold requirement.

**Goal requirements:**

This is a goal requirement.

Notes:

1. This is a note.

# Introduction

---

This section aims to provide background and specific information on the processing steps that can be used to achieve analysis ready data for a specific and well-developed Product Family Specification. This Guidance material does not replace or override the specifications.

## What is CEOS Analysis Ready Data?

---

CEOS-ARD are products that have been processed to a minimum set of requirements and organized into a form that allows immediate analysis with a minimum of additional user effort. In general, these products would be resampled onto a common geometric grid (for a given product) and would provide baseline data for further interoperability both through time and with other datasets.

CEOS-ARD products are intended to be flexible and accessible products suitable for a wide range of users for a wide variety of applications, including particularly time series analysis and multi-sensor application development. They are also intended to support rapid ingestion and exploitation via high-performance computing, cloud computing and other future data architectures. They may not be suitable for all purposes and are not intended as a *replacement* for other types of satellite products.

## When can a product be called CEOS-ARD?

---

The CEOS-ARD branding is applied to a particular product once:

- that product has been assessed as meeting CEOS-ARD requirements by the agency responsible for production and distribution of the product, and
- that the assessment has been peer reviewed by the relevant CEOS team(s).

Agencies or other entities considering undertaking an assessment process should consult the [CEOS-ARD Governance Framework](#).

A product can continue to use CEOS-ARD branding as long as its generation and distribution remain consistent with the peer-reviewed assessment.

## What is the difference between Threshold and Goal?

---

**Threshold** (Minimum) requirements are the **minimum** that is needed for the data to be analysis ready. This must be practical and accepted by the data producers.

**Goal** (Desired) requirements (previously referred to as “Target”) are the ideal; where we would like to be. Some providers may already meet these.

Products that meet all *threshold* requirements should be immediately useful for scientific analysis or decision-making.

Products that meet *goal* requirements will reduce the overall product uncertainties and enhance broad-scale applications. For example, the products may enhance interoperability or provide increased accuracy through additional corrections that are not reasonable at the *threshold* level.

Goal requirements anticipate continuous improvement of methods and evolution of community expectations, which are both normal and inevitable in a developing field. Over time, *goal* specifications may (and subject to due process) become accepted as *threshold* requirements.

## References

---

International Organization for Standardization. 2009. "Geographic information — Metadata — Part 2: Extensions for imagery and gridded data." Standard. Geneva, CH: International Organization for Standardization.

Li, Fuqin, David L. B. Jupp, Medhavy Thankappan, Leo Lymburner, Norman Mueller, Adam Lewis, and Alex Held. 2012. "A Physics-Based Atmospheric and BRDF Correction for Landsat Data over Mountainous Terrain." *Remote Sensing of Environment* 124: 756–70.  
<https://doi.org/https://doi.org/10.1016/j.rse.2012.06.018>.